



Vinyl Luxury vinyl tiles

enduro[®]



creating better environments

Forbo

FLOORING SYSTEMS



enduro[®]

Forbo Enduro is an LVT offer that creates many possibilities. All the items in the range are available in a Dryback with a 0.30 wear layer and semi-rigid Click with an 0.55 wear layer and an integrated acoustic underlay. This Click product offers flexibility and high acoustic performance and is quick to install through this integrated underlay. Enduro offers you the possibility to use the right material for the job at hand.

The product has been designed by Forbo to reflect relevant design and colours of today that can be used either individually or in nice combinations across colours and design. We can assure that both products are delivering the expected performance when installed properly. For details and inspiration please check the Forbo Flooring website.



enduro®





white oak
69102DR3 | 121,9 x 17,8 cm
69102CD5 | 121,2 x 18,5 cm | 



washed oak
69100DR3 | 121,9 x 17,8 cm
69100CD5 | 121,2 x 18,5 cm | 



pure oak
69101DR3 | 121,9 x 17,8 cm
69101CD5 | 121,2 x 18,5 cm | 



light timber
69335DR3 | 121,9 x 17,8 cm
69335CD5 | 121,2 x 18,5 cm | 



natural timber
69330DR3 | 121,9 x 17,8 cm
69330CD5 | 121,2 x 18,5 cm | 



anthracite timber
69336DR3 | 121,9 x 17,8 cm
69336CD5 | 121,2 x 18,5 cm | 



natural white oak
69130DR3 | 121,9 x 17,8 cm
69130CD5 | 121,2 x 18,5 cm | 



natural warm oak
69135DR3 | 121,9 x 17,8 cm
69135CD5 | 121,2 x 18,5 cm | 



natural grey oak
69137DR3 | 121,9 x 17,8 cm
69137CD5 | 121,2 x 18,5 cm | 



light oak
69124DR3 | 121,9 x 17,8 cm
69124CD5 | 121,2 x 18,5 cm | 



golden oak
691202DR3 | 121,9 x 17,8 cm
69120CD5 | 121,2 x 18,5 cm | 



natural nutwood
69206DR3 | 121,9 x 17,8 cm
69206CD5 | 121,2 x 18,5 cm |



white pine
69184DR3 | 121,9 x 17,8 cm
69184CD5 | 121,2 x 18,5 cm |



steamed pine
69186DR3 | 121,9 x 17,8 cm
69186CD5 | 121,2 x 18,5 cm |



dark nutwood
69209DR3 | 121,9 x 17,8 cm
69209CD5 | 121,2 x 18,5 cm |



light concrete
69203DR3 | 60,96 x 30,48 cm
69203CD5 | 61 x 30,5 cm |



beige concrete
69204DR3 | 60,96 x 30,48 cm
69204CD5 | 61 x 30,5 cm |



mid concrete
69202DR3 | 60,96 x 30,48 cm
69202CD5 | 61 x 30,5 cm |



Technical specifications

Enduro Dryback meets the requirements of EN ISO 10582

Enduro Click Decibel meets the requirements of EN ISO 16511

Enduro Click Decibel meets the requirements of EN ISO 16511		Enduro Dryback	Enduro Click Decibel	
	Total thickness	EN ISO 24346	2.0 mm	5.0 mm
	Wear layer thickness	EN ISO 24340	0.30 mm	0.55 mm
	Collection size		18	18
	Domestic use	EN ISO 10874	Class 23	Class 23
	Commercial use	EN ISO 10874	Class 31	Class 33
	Tile size	EN ISO 24342	60.96 x 30.48 cm	61 x 30.5 cm
	Plank size	EN ISO 24342	121.9 x 17.8 cm	121.2 x 18.5 cm
	Packaging per carton tiles		4.09 m² (22 pcs)	1.86 m² (10 pcs)
	Packaging per carton planks		4.77 m² (22 pcs)	1.79 m² (8 pcs)
	Squareness and straightness	EN ISO 24342	< 400 mm < 0.25 mm > 400 mm < 0.35 mm	< 400 mm < 0.25 mm > 400 mm < 0.35 mm
	Total weight	EN ISO 23997	ca. 3000 g/m²	ca. 6300 g/m²
	Wear layer binder content	EN ISO 10582	Type 1	Type 1
	Castor chair continuous use	ISO 4918	Good	Good
	Slip resistance (ramp test)	DIN 51130	R10	R10
	Acoustical impact noise reduction	EN ISO 717-2	5 dB	19 dB
	Residual indentation	EN ISO 24343-1	≤ 0.10 mm	≤ 0.10 mm
	Colour fastness to light	EN ISO 105-B02 method 3	≥ 6	≥ 6
	Resistance to chemicals	EN ISO 26987	Good	Good
	Dimension stability	EN ISO 23999	≤ 0.10%	≤ 0.10%
	Indoor air emissions: TVOC after 28 days	EN 16516	≤ 0.01 mg/m³	≤ 0.01 mg/m³
	Recycled content (mass)		25%	25%
Enduro meets the requirements of EN 14041:2004				
	Reaction to fire	EN 13501-1	B _f s1, G, CS	B _f s1, L, CS
	Slip resistance	EN 13893	μ ≥ 0.30	μ ≥ 0.30
	Thermal conductivity	EN 12524	0.25 W/mK	0.25 W/mK
	Body voltage	EN 1815	≤ 2.0 kV	≤ 2.0 kV

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.



Find us on



creating better environments

Forbo Flooring B.V.
P.O. Box 13
1560 AA Krommenie
The Netherlands
T: +31 75 647 74 77
E-mail: question@forbo.com
www.forbo-flooring.com



FLOORING SYSTEMS