KN/K

SUPERPLASMA AQ CE

WHE00104





TECHNICAL DETAILS



MATERIAL

EXTERNAL SHELL: HD Polypropylene

INTERNAL SHELL: HD Polystyrene

HEADBAND: Soft PA Nylon



Universal-adjustable from 51 to 63 cm



WEIGHT

390 g



STANDARD

EN 397

Protection against front, rear and side impacts in conformity with EN 12492 Clauses 4.2.1.2, 4.2.1.3, 4.2.1.4 shock energy absorption capacity Clause 4.2.2 penetration Clause 4.1.4 ventilation

EN 397 ADDITIONAL TESTS: -30°C/LD/MM

WHE00104-201 WHITE		WHE00104-202 YELLOW		WHE00104-203 ORANGE
WHE00104-204 RED	•	WHE00104-205 GREEN	•	WHE00104-206 BRITISH GREEN
WHE00104-207 ROYAL		WHE00104-208 BLUE	•	WHE00104-210 BLACK
WHE00104-214 PINK				



TEMPERATURE OF USE

-30°C/+50°C



TECHNOLOGIES





A quick-drying fabric with moisture-wicking technology that accelerates the dispersion of sweat to the surface of the helmet padding for a drier, more comfortable wear.



ANTI-INTRUSION MESH



Metal mesh vent covers that prevent debris from entering the helmet while maintaining breathability.



EARMUFF ADAPTER ATTACHMENT POINTS

Helmet designed with attachment points for earmuff adapters.



RING TO HOOK

Designed with 4 built-in, nylon lamp attachment points. Compatible with KASK headlamps and other headlamps with elastic bands.



Chinstrap loop that enables the wearer to securely attach the helmet to a harness or other items.



VENTILATION CHANNELS

INTEGRATED LAMP CLIPS

Designed with 10 air intakes and internal channels for enhanced breathability and wearer comfort.



ECO-LEATHER CHINSTRAP





VISOR ATTACHMENT POINTS

Helmet designed with attachment points for securing KASK compatible visors.



ERGO FIT SYSTEM

Helmet size adjusting system that allows for an easy and secure fit by turning the large diameter dial. The ergonomically shaped rear piece cradles the back of the neck for added comfort.













KAJK

PERFORMANCES

Protection against top impacts	K	5 kg from 1 m 50 J
Protection against side, front and rear impacts	K*	5 kg from 0,5 m 25 J
Protection against the penetration of objects	K	3 kg from 1 m 30 J
Chinstrap release	K	>15 kg <25 kg

Lower temperature resistance test	K**	T=-30°C
Protection against side deformation	K**	
Protection against molten metal splashes	K **	

K Required performance tests

K* Additional test in conformity with EN 12492 requirements

K** Additional tests performed to meet optional requirements

ADDITIONAL INFORMATION

GUARANTEE

3 years starting from the date of purchase.

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachments, deformities, or peeling that represent factual elements of the state of deterioration of the helmet. Helmets that have suffered a severe impact shall be replaced even if they do not show obvious signs of damage.

CLEANING

Clean the helmet with the KASK Helmet cleaner or with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). The KASK Liner Refresher is available to neutralise unpleasant odours.

The helmet should be stored away from direct sunlight or source of heat. We recommend the use of the KASK drawstring helmet bag to protect the helmet when not in use.

ADHESIVE APPLICATION

Do not apply adhesives, stickers or use paint and solvents on the helmet that do not comply with the manufacturer's specifications. Any alteration or intervention may impair its protective function.

SAFETY ACCESSORIES



WVI00018 VISOR V2 PLUS



WVI00024



WVI00003



WVI00006



WHP00004/5/6



WAC00036/37 SUN SHIELD

DISCOVER MORE



SCAN FOR COMPLETE COLLECTION





WAC00020/24 NECK SHADE



WAC00032/33 NECK SHIELD RW











© 2022 KASK SPA. All rights reserved